



3.100 W




260° C



36 Kg.



230 V - 50 Hz



w 640 d 720 H 540

CARACTERÍSTICAS features

- | | |
|---|--|
| <ul style="list-style-type: none"> ● DIMENSIONES INTERNAS: (W)500x(D)410x(H)345 mm
<i>cooking chamber dimension</i> ● DIMENSIONES EXTERNAS: (W)640x(D)720x(H)540 mm
<i>external dimension</i> ● DISTANCIA ENTRE PARRILLAS: 80 mm.
<i>distance between trays</i> ● CONEXIÓN: SCHUKO_MONOFASICO <i>single phase connection</i> ● DOTACIÓN: 4 Parrillas
<i>including: 4 wire rack</i> | <ul style="list-style-type: none"> ● POTENCIA: 3.100 W
<i>power</i> ● TEMPERATURA MÁXIMA: 260° C
<i>max temperature</i> ● PESO: 35 Kg.
<i>weight</i> ● VOLTAJE: 230 V / 50 Hz
<i>Voltage</i> |
|---|--|

EQUIPAMIENTO equipment

- | | |
|--|--|
| <ul style="list-style-type: none"> ● Alarma fin de ciclo <i>Cycle end alarm</i> ● Micro de puerta <i>Door safety switch</i> ● Termostato de seguridad <i>Safety thermostat</i> ● Lámpara interior <i>Halogen chamber light</i> | <ul style="list-style-type: none"> ● Conexión agua ¼ <i>Water connection ¼</i> ● Humedad regulable 0-100% <i>Adjustable humidity 0% – 100 %</i> ● 99 Programas con tres fases cada uno <i>99 programs with three phases each</i> ● Precalentamiento automatico <i>Automatic pre-heating system</i> ● Apertura reversible modelo (puerta lateral)
<i>Reversible opening door (side door model) (RXL)</i> |
|--|--|

OPCIONES (PVP) options (rrp)

- KIT GN 2/3

PVP rrp ME-424

PVP rrp ME-424-L